

PURCHASER	P.O. #	DATE
PROJECT	LOCATION	
ENGINEER	ARCHITECT	
SUBMITTED BY	FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING BTU/H	VOLTAGE	FRIEDRICH MODEL

COMPACT SIZE FOR EASIER REMOVAL AND STORAGE | 5,500 to 11,700 BTU/h EERs up to 11.5

DIGITAL CONTROL FEATURES

- 24-hour timer lets you program on/off times
- 3 cooling speeds, plus fan-only setting
- MoneySaver® setting saves energy by cycling the fan with the compressor
- Smart Fan adjusts fan speed to maintain desired temperature
- Unique Comfortwatch technology
- Memory backup saves settings if power is interrupted

FITS WINDOWS- MINIMUM: 26" WIDE. MAXIMUM: 42" WIDE

DELUXE FEATURES




- Ultraquiet operation
- 8-way air flow control
- Slide-out chassis for more permanent window or wall installation
- Washable, antimicrobial filter for protection against fungal and bacterial growth
- Heavy duty side curtains reduce exterior noise/ light
- Rust proof base pan



THE INDUSTRY'S SMALLEST SLIDE-OUT CHASSIS- MODEL XQ05

ONE TOUCH OPERATION	REMOTE CONTROL	24 HR. TIMER	MONEY SAVER FEATURE	SMART FAN	ANTIMICROBIAL FILTER	SLIDE-OUT CHASSIS
✓	✓	✓	✓	✓	✓	✓

Specifications ENERGY STAR® Models


Model	Cooling Capacity BTU/h	Heating Capacity Rated	Electrical Characteristics (60 Hertz)				Energy Efficiency Ratio EER	Moisture Removal Pints/Hr.	Room Side Air Circulation CFM	Sleeve*	Net Weight Lbs.	
			Volts Rated	Cooling Amps	Cooling Watts	Heating Amps						Heating Watts
COMMERCIAL GRADE												
XSTAR												
 XQ05L10A	5500	—	115	5.0	500	—	—	11.0	1.2	200	Q	70
 XQ06L10A	6300	—	115	4.9	548	—	—	11.5	1.4	175	Q	70
 XQ08L10A	8000	—	115	6.8	741	—	—	10.8	1.9	175	Q	77
XQ10L10A	10000	—	115	9.0	1000	—	—	10.0	3.2	180	Q	83
XQ12L10A	11700	—	115	11.0	1198	—	—	9.8	3.2	200	Q	83

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.

Installation Information / Sleeve Dimensions

Sleeve	Height	Width	Depth with Front	Depth Hood to Louvers	Minimum Extension Into Room	Minimum Extension Outside	Window Width		Thru-the-wall Finished Hole	
							Minimum	Maximum	Height	Width
Q	14"	19 ¾"	21 ¾"	8 ½"	5 ½"	10 ¾"	26"	42"	14 ¼"	20"

Circuit Rating/ Breaker

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Wall Outlet Appearance
All XQ MODELS.	125V - 15A	5 - 15P	



 As an ENERGY STAR® partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR® () models meet the ENERGY STAR® guidelines for energy efficiency.



The consumer- through the AHAM Room Air Conditioner Certification Program- can be certain that the AHAM Certification Seal accurately states the unit's cooling and heating capacity rating, the amperes and the energy efficiency ratio.

Friedrich

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>